

PC4 Migration Quick Glance

Americas

Printer Configuration(1)	Replaces	Printing Method / Media	Resolution (DPI)	Connectivity (standard)	Printer Language
PF8DA03000000	PC4*00000000 PC4*00010000 (1)	DT	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03100000 [NEW]	PC4*00100000 PC4*00110000 (1)	DT or TTR (0.5"/12.7mm core)	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03101000 [NEW]	PC4*00101000 PC4*00001000 PC4*00011000 (1) PC4*00301000 (2) PC4*00111000 (1)	DT or TTR (0.5"/12.7mm core)	300	Serial, Parallel & USB	ESIM (EPL)
PF8TA03000000	none	DT or TTR (1.0"/25.4mm core)	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03001000	PC4*00001000 PC4*00011000 (1)	DT or TTR (1.0"/25.4mm core)	300	Serial, Parallel & USB	ESIM (EPL)
PC41A000000	none	DT	203	Serial, Parallel & USB	IPL
PC41A001000	none	DT or TTR (0.5" core)	203	Serial, Parallel & USB	IPL

(1) Field-installable options: Cutter, Self-Strip, Ethernet, 1GB Flash with RTC (PF8t only)

(2) The PF8 printers can print on label stock up to 0.18mm (180 microns) in thickness

Americas (U.S.) power cord p/n 226-000001-200

* = A, B, or C (PC4A, PC4B, PC4C)